Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

1. (currently amended) A mud box having an open end and a peripheral sidewall, a plurality of resilient spring legs attached to said box, said legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface, said free end portions being spaced-apart a distance greater than the maximum distance across said peripheral sidewall so that the free end portions extend outwardly beyond the peripheral sidewall.

2. (original) The box of claim 1 wherein said box has a bottom wall opposite from said open end, said spring legs being attached to said bottom wall.

3. (currently amended) The box of claim 2 wherein said box is molded of plastic material and said bottom wall has an external attachment projection molded integrally therewith to which said spring legs are attached.

Claims 4-10 (cancelled).

11. (currently amended) A mud box molded of plastic material, said box having a bottom wall and an open end opposite from said bottom wall, said bottom wall having an external surface, and an attachment device molded integrally with [[formed on]] said bottom wall on said external surface thereof for attaching support legs to said box, said attachment device being centrally located on said bottom wall and extending outwardly from said external surface thereof.

Claims 12-14 (cancelled).

15. (currently amended) The box of claim 12 wherein said projection has a central cylindrical portion and a transverse projection portion that is spaced outwardly from said bottom wall external surface, said projection having a length in one direction perpendicular to said cylindrical portion that is greater than its width in a second direction perpendicular to said one direction.

16. (currently amended) The box of claim 15 including a generally U-shaped spring member having a central attachment portion with an attachment opening configured for receiving said attachment projection therethrough, said transverse projection extending outwardly of said attachment opening to engage portions of said attachment portion around said attachment opening and retain said spring leg member on said box.

Claims 17-24 (cancelled).

25. (currently amended) A support kit for attachment to an electrical mud box, said kit including a pair of generally U-shaped spring leg members, each spring leg member having a central attachment portion with an attachment opening therethrough, and each spring leg member having a pair of legs diverging outwardly from said attachment portion and terminating in leg end portions that are spaced-apart a distance greater than the length of said central attachment portion.

26. (original) The kit of claim 25 wherein said attachment portion is generally flat and said attachment opening is elongated along the length of said attachment portion.

27. (original) The kit of claim 25 including a flat bendable strap having a central attachment opening therethrough.

28. (original) The kit of claim 27 wherein said attachment opening in each of said spring members corresponds in size and shape to the size and shape of said attachment opening in said strap.

29. (new) A mud box having an open end and a bottom wall opposite from said open end, said bottom wall having an external attachment projection, a plurality of abutments on said bottom wall spaced outwardly from said projection and forming abutment guideways therebetween, a plurality of resilient spring legs having attachment portions that are received in said abutment guideways and have attachment openings received over said attachment projection to attach said spring legs to said box, said spring legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface.

30. (new) The box of claim 29 wherein at least two of said abutments have cam surfaces engageable by at least one of said attachment portions of said spring legs to cam said one attachment portion past said two abutments when said one attachment portion is placed over said projection and rotated 90°.

31. (new) A mud box having an open end, a plurality of resilient spring legs attached to said box, said legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface, and an elongated bendable strap attached to said box for attachment to reinforcement rods between spaced forms.

32. (new) A mud box having an open end, a plurality of resilient spring legs attached to said box, said legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface, said spring legs being defined by a pair of spring members, each spring member having a central attachment portion with a pair of spring legs extending therefrom, and said attachment portions being attached to said box in perpendicular relationship to one another to provide four spaced-apart spring legs extending outwardly from said box.

33. (new) The box of claim 32 including a box projection having an enlarged head, said attachment portions having openings for receiving said head, and said head and said opening in at least one of said attachment portions being shaped to provide reception of said head through said opening and to prevent withdrawal of said head from said opening after said one attachment portion is rotated 90°.

34. (new) A mud box having an open end, a plurality of resilient spring legs attached to said box, said legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface, said spring legs supporting said box between a pair of spaced-apart parallel concrete forms with inner form surfaces spaced-apart between 6-8 inches.

35. (new) A mud box having an open end, a plurality of resilient spring legs attached to said box, said legs having free end portions engageable with one form surface for biasing said box in a direction to engage said box open end with an opposite form surface, each spring leg having a reversely curved bifurcated end portion to provide a pair of spaced-apart reversely curved support end portions each of which has a width that is not greater than the space between them.

36. (new) A mud box having a bottom wall and an open end opposite from said bottom wall, said bottom wall having an external surface, a centrally located attachment projection integrally formed on said external surface and extending outwardly therefrom for attaching support legs to said box, and a plurality of abutments on said external surface of said bottom wall spaced outwardly from said attachment projection and forming abutment guideways that extend perpendicular to one another past said attachment projection.

37. (new) The box of claim 36 wherein at least two of said abutments have cam surfaces that slope downwardly toward one of said guideways.

38. (new) A support kit for attachment to an electrical mud box, said kit including a pair of generally U-shaped spring leg members and a flat bendable strap, each spring leg member having a central attachment portion with an attachment opening therethrough, and said strap having a central attachment opening therethrough.

39. (new) The kit of claim 38 wherein said attachment opening in each of said spring members corresponds in size and shape to the size and shape of said attachment opening in said strap.

40. (new) An electrical box molded of plastic material, said box having a bottom wall with an external surface, a centrally located projection molded integrally with said bottom wall and extending outwardly from said external surface thereof, at least one flat bendable metal strap having an opening therethrough, said projection and said opening being configured for reception of said projection through said opening in an alignment orientation of said projection and opening, and said projection and opening being configured for preventing movement of said projection through said opening when said strap and projection are rotated out of said alignment orientation with said projection extending through said opening.

41. (new) The box of claim 40 including a pair of flat bendable straps extending perpendicular to one another.

42. (new) The box of claim 40 wherein said opening has the general configuration of a double keyhole and said projection is configured for close reception therethrough.

43. (new) An electrical box molded of plastic material, said box having a bottom wall with an external surface, a pair of elongated flat bendable metal straps, said external surface and said metal straps being configured for attachment of said straps to said bottom wall with said straps extending generally perpendicular to one another in overlying relationship.

44. (new) The box of claim 43 wherein said external surface has a projection thereon and said straps have openings through which said projection is receivable, said straps being positionable in overlying aligned inner and outer relationship for reception of said projection through said strap openings, and said outer strap being rotatable 90° relative to said inner strap to move said opening in said outer strap out of aligned relationship with said projection so that said projection no longer is movable through said opening in said outer strap to thereby hold said pair of straps to said bottom wall.

45. (new) An electrical box of plastic material, said box having a bottom wall with an external surface, a projection extending outwardly from said external surface, said projection having an enlarged head spaced outwardly from said external surface, a pair of elongated flat bendable metal straps having openings therethrough, said openings being configured for receiving said enlarged head therethrough, said enlarged head and at least one of said openings on at least one of said straps being configured to provide reception of said enlarged head through said one opening and to prevent withdrawal of said head from said opening after rotating said one strap about said projection.

46. (new) The box of claim 45 wherein said straps support said box between a pair of spaced-apart concrete forms that have inner form surfaces spaced-apart between 6-8 inches, said box having an open end and said straps supporting said box between said forms with said open end positioned closely adjacent to or in engagement with one of said form inner surfaces.